

Digital Mini Clamp Meters CHB 130 & 140 (AC)



93520

Key Functions

- Current measurement

General Information

- Manual selection of measurement range
- Clamp Opening 28 mm
- Handy, extra small current clamp facilitates measurements in locations difficult to access
- Appropriate for basic workshop equipment

Special Features

- Extraordinary price-performance ratio

Technical Data

Display	3 1/2 digit, LCD, 1999 Digits
Measurement Range	
Current AC:	0,01...300 A
Resolution:	0,01 A, 0,1 A, 1 A
Tolerance:	± (2 %rdg. + 3 Digit)
Frequency Range:	50...60 Hz
Measurement Category	CAT III / 600 V
Pollution Degree:	2
Protection Class:	IP 40
Safety in compl. With:	IEC 61010, EN 61010, DIN VDE 0411
Clamp Opening:	ø 28 mm
Power Supply:	1 x 9 V, IEC 6LR61
Dimensions:	65 x 185 x 35 mm
Weight approx.:	175 g



93532

Key Functions


- Current voltage resistance and frequency measurement

General Information

- Manual selection of measurement range
- Integrated data hold
- Clamp Opening 28 mm
- Handy, extra small current clamp facilitates measurements in locations difficult to access
- Auto-Power-Off
- Appropriate for basic workshop equipment

Technical Data

Display :	3 3/4 digit, LCD, 3999 Digits
Measuring Ranges	
Current AC:	0,01...400 A
Tolerance:	± (2% rdg. + 5 D)
Voltage AC:	0,1...600 V
Tolerance:	± (1,2 % rdg. + 5 D)
Voltage DC:	0,1...600 V
Tolerance:	± (1,2 % rdg. + 5 D)
Continuity:	R < 40 Ω
Input Resistance:	1 MΩ
Resistance:	0,1Ω...400Ω
Tolerance:	± (1% rdg. + 5 D)
Frequency Range for Current/Voltage AC	50...400 Hz
Pollution Degree:	2
Measurement Category:	CAT II / 600 V
Safety in compl. With:	VDE 0411, EN 61010, IEC 61010
Clamp opening:	ø 28 mm
Power supply:	2 x 1.5 V IEC LR03
Dimensions:	185 x 65 x 35 mm
Weight approx.:	175 g



Vaiseshika Electron Devices
38, Industrial Estate, Ambala Cantt-133 001
Phone: (171) - 2699827, 2699891, Fax: 2699773
Email: vaiseshika@gmail.com

