

**DIGITAL CLAMP METER
(AC/DC)**



93539



Key Functions

- Current voltage and resistance measurement
- Acoustical continuity test

General Information

- Automatic and manual selection of measurement range
- Integrated data hold
- Clamp opening 30 mm

Special Features

- AC/DC current clamps are also appropriate for the use in automobile workshops, UPSs and solar technology

TECHNICAL DATA

Display	: 3½ Digit, LCD, 3999 Digit
Measuring Ranges	
Current AC	: 0.01...400 A
Tolerance	: ± (2% rdg. + 10 Digit)
Current DC	: 0.01 ... 400 A
Tolerance	: ± (2.5% rdg. + 10 Digit)
Voltage AC	: 0.1 mV...600 V
Tolerance	: ± (1% rdg. + 3 Digit)
Voltage DC	: 0.1 mV...600 V
Tolerance	: ± (0.8% rdg. + 2 Digit)
Input Resistance	: 10MΩ
Frequency Range for Current/Voltage AC	: 50...500 Hz
Resistance	: 0.1Ω ... 40MΩ
Tolerance	: ± (1% rdg. + 3 Digit)
Continuity	: R < 30 Ω
Pollution Degree	: 2
Measurement Category	: CAT II/600 V
Safety Complying with	: EN61010, IEC61010
Clamp opening	: Ø 30mm
Power Supply	: 2 x 1.5 V, IEC LR 03
Dimensions	: 195 x 64 x 30 mm
Weight	: approx. 240 g.

